

**MAYTAG**

## TECHNICAL SPECIFICATIONS

*Model CSH4BD Series*



M120 Product Line

**R-410A High Efficiency Heat Pump  
13 SEER — 1.5 - 5 Ton Capacity**

Maytag now offers the choice of a heat pump that uses a more efficient and environmentally friendly refrigerant designated R-410A. The CSH4BD Series of heat pumps offers exceptional performance from a small, compact package. The unit, when combined with our engineered coils or air handlers, offers a full line of quality, split system cooling equipment.


### Features and Benefits

- **Smart Cool 410™ Refrigerant (R-410A)** – Earth friendly non-ozone depleting refrigerant.
- **Quiet Plus™ Sound Package** – Consists of a Quiet Plus™ Compressor Sound Blanket and Swept Wing Fan Blade. Both have been engineered to significantly reduce unwanted noise.
- **Durable, Attractive Cabinet** – Designed using galvanized steel with a polyester urethane finish. The 950 hour salt spray finish is 1.5 mil thick and resists corrosion 50% better than comparable units.
- **Copper Tube / Aluminum Fin Coils** – Coils are designed to optimize heat transfer, minimize size and cost, and increase durability and reliability.
- **Permanently Lubricated Motor** – A heavy duty PSC motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Removable Top Grille Assembly** – Allows ease of service from the top without disconnecting fan motor leads.
- **High Pressure Switch** – Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Liquid Line Filter / Drier** – Included with unit, field installed.
- **One Piece Top/Orifice** – Designed for maximum airflow and quiet operation.
- **Five Minute Restart Time Delay** – When the unit shuts down, a five minute delay keeps the unit from restarting, eliminating the highest cause for compressor failure.
- **Easy Compressor and Control Access** – Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **Composite Base Pan** – Absorbs sound and is corrosion resistant. Composite is also stronger and lighter than steel.




## DIMENSIONS/OUTDOOR SECTION

CSH4BD-	018K	024K	030K	036K	042K	048K	060K
H	33 1/2	37 1/2	41 1/2	45 1/2	41 1/2	45 1/2	45 1/2
W	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4
D	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4



## IDENTIFICATION CODE



# PHYSICAL AND ELECTRICAL SPECIFICATIONS / OUTDOOR UNITS

## 13 SEER — High Efficiency — Single Phase

Model Number CSH4BD		018K	024K	030K	036K	042K	048K	060K	
Electrical Data	Volts-Cycles-Phase (1)	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	
	Total Amps	10.2	14.6	15.3	17.8	19.4	23.2	27.7	
	Delay Fuse Max. (2)	20	30	30	35	40	50	60	
	Min. Circuit Ampacity	12.4	18.0	18.8	22.0	23.9	28.7	34.3	
Condenser Data	Coil	Area	17.7	20.3	22.8	25.3	22.8	25.3	25.3
		Rows-FPI	1-18	1-18	1-20	1-20	2-16	2-16	2-16
		Tube Dia	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.
	Fan Motor	Type	PSC	PSC	PSC	PSC	PSC	PSC	PSC
		Amps	1.2	1.2	1.2	1.2	1.46	1.46	1.46
		HP	0.2	0.2	0.2	0.2	0.25	0.25	0.25
	Fan Blade	Dia - # Blades	24" - 2	24" - 2	24" - 2	24" - 2	24" - 2	24" - 2	24" - 2
		SCFM	3000	3200	3300	3400	3700	3800	3800
	Compressor Data	RLA	9.0	13.4	14.1	16.6	17.9	21.8	26.2
		LRA	48.0	58.3	73.0	79.0	112.0	117.0	134.0
Refrigerant suction line O.D. Note: Liquid line is 3/8" O.D. for entire length	0-24 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	7/8"	
	25-39 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)	
	40-75 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)	
Approximate Weight (lbs.)	Net	166	171	176	181	247	280	290	
	Ship	175	180	185	190	260	295	305	
Sound Rating db		67	67	67	69	71	71	71	

(1) Operating Voltage Range: 187v min. - 253v max.

(2) HACR Type Circuit Breakers may be used.

(3) Requires 7/8" to 1-1/8" reducer from line to unit.

(4) Additional charge for line sets above 15 feet.

Values based on suction line as follows with 3/8" liquid line.

a) 3/4" = 0.6 oz. per additional foot.

b) 7/8" = 0.7 oz. per additional foot.

c) 1 1/8" = 0.8 oz. per additional foot.

## ACCESSORIES - CONDENSING UNIT

### Start Assist Kit - 912933

Provides additional starting torque for the compressor motor when operating with low line voltage or high operating temperatures.

### Outdoor Thermostat - 913852

Two stage logic provides ability to lock out electric strips down to balance point and bring on in stages.

### Fan Delay Kit (TDR)

**918476** - 80 second fan delay

### Extreme Wind Condition Mounting Kit - 920900

### Snow Stand Kit - 920636

# SYSTEM COOLING CAPACITIES

## 13 SEER — High Efficiency — Single Phase

Outdoor Unit Model Number CSH4BD	Indoor Unit Model Number C6B(A,H)-	Cooling Capacity Btuh	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	Nominal SCFM
018K	B6BMM024K-A	17,500	13.00	11.00	19,000	8.00	650
018K	B6BMM024K-B	17,500	13.00	11.00	17,700	7.70	650
024K	B6BMM024K-A	23,000	13.00	11.00	24,800	8.00	850
024K	B6BMM024K-B	23,000	13.00	11.00	26,000	8.00	820
030K	B6BMM030K-A	28,800	13.00	11.00	30,800	8.00	900
030K	B6BMM030K-B	28,800	13.00	11.00	29,000	8.00	1075
036K	B6BMM036K-B	34,800	13.00	11.00	36,800	8.00	1170
042K	B6BMM042K-B	40,000	13.00	11.00	42,000	7.80	1495
048K	B6BMM048K-B	46,500	13.00	11.00	49,500	8.00	1360
048K	B6BMM048K-C	47,500	13.00	11.00	47,500	8.00	1620
060K	B6BMM060K-C	57,500	13.00	11.00	60,500	8.00	1660

Outdoor Unit CSH4BD	Indoor TXV Coil + TDR	Cooling Capacity BTUH	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	SCFM
018K	C7B(A,H)M01824(C,U)-A	18,000	13.00	11.00	18,000	8.00	580
018K	C7B(A,H)M01824(C,U)-B	18,000	13.00	11.00	18,000	8.00	580
024K	C7B(A,H)M01824(C,U)-A	22,800	13.00	11.00	23,600	8.00	805
024K	C7B(A,H)M01824(C,U)-B	22,800	13.00	11.00	23,600	8.00	855
030K	C7B(A,H)M03036(C,U)-A	28,400	13.00	11.00	29,000	8.00	1005
030K	C7B(A,H)M03036(C,U)-B	28,400	13.00	11.00	29,000	8.00	1005
030K	C7B(A,H)M030(C,U)-C	28,400	13.00	11.00	29,000	8.00	1005
036K	C7B(A,H)M03036(C,U)-B	34,600	13.00	11.00	36,000	8.00	1180
036K	C7B(A,H)M03642(C,U)-B	34,600	13.00	11.00	36,000	8.00	1180
036K	C7B(A,H)M03648(C,U)-C	34,600	13.00	11.00	36,000	8.00	1180
042K	C7B(A,H)M03642(C,U)-B	39,000	13.00	11.00	41,500	8.00	1320
042K	C7B(A,H)M03648(C,U)-C	39,000	13.00	11.00	41,500	8.00	1320
042K	C7B(A,H)M042(C,U)-D	39,000	13.00	11.00	41,500	8.00	1320
048K	C7B(A,H)M03648(C,U)-C	45,500	13.00	11.00	47,000	8.00	1395
048K	C7B(A,H)M048(C,U)-C	45,500	13.00	11.00	47,000	8.00	1325
048K	C7B(A,H)M048(C,U)-D	45,500	13.00	11.00	47,000	8.00	1325

See current AHRI Directory for certified combinations and ratings  
[www.ahridirectory.org](http://www.ahridirectory.org)

## 13 SEER + LOOSE COIL COOLING EXPANDED RATINGS

### CSH4BD018K C7B(A,H)M01824(C,U)-A

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	19.1	15.1	1.14	18.3	14.9	1.27	17.4	14.9	1.40	16.4	14.6	1.55	15.18	14.92	1.71	14.35	14.10	1.90
	80	67	21.1	12.2	1.16	20.2	12.1	1.28	19.2	12.2	1.42	18.2	12.0	1.57	16.97	11.70	1.73	15.64	10.75	1.91
	80	72	23.4	9.5	1.19	22.4	9.5	1.31	21.4	9.7	1.45	20.3	9.4	1.60	19.06	9.24	1.76	17.72	9.41	1.94
	75	63	19.4	11.8	1.14	18.6	11.7	1.27	17.6	11.7	1.41	16.6	11.4	1.55	15.23	10.29	1.71	14.19	11.10	1.90
600	80	62	19.7	16.3	1.17	18.9	16.6	1.30	17.9	16.2	1.44	16.9	15.9	1.58	16.07	15.53	1.75	14.87	14.75	1.93
	80	67	21.7	13.1	1.19	20.7	13.4	1.32	19.7	13.1	1.45	18.6	12.9	1.60	17.37	12.81	1.76	16.02	12.69	1.95
	80	72	24.0	10.1	1.22	23.0	10.5	1.35	21.9	10.2	1.49	20.7	10.1	1.64	19.45	10.10	1.79	18.06	10.11	1.98
	75	63	19.9	12.6	1.17	19.0	12.9	1.30	18.1	12.5	1.44	17.0	12.3	1.58	15.75	12.14	1.75	14.46	12.17	1.93
675	80	62	20.2	17.7	1.20	19.4	17.8	1.33	18.6	17.3	1.47	17.7	16.8	1.62	16.69	16.12	1.78	15.58	15.51	1.97
	80	67	22.0	14.1	1.22	21.1	14.2	1.35	20.1	13.9	1.49	18.9	13.8	1.63	17.66	13.60	1.80	16.37	13.85	1.98
	80	72	24.4	10.8	1.26	23.4	11.0	1.39	22.2	10.7	1.52	21.0	10.7	1.67	19.73	10.62	1.83	18.26	10.70	2.01
	75	63	20.3	13.6	1.20	19.4	13.7	1.33	18.4	13.3	1.47	17.3	13.1	1.61	16.12	13.16	1.78	14.65	12.98	1.96



# 13 SEER + LOOSE COIL COOLING EXPANDED RATINGS (CONTINUED)

**CSH4BD048K C7B(A,H)M03648(C,U)-C**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	48.8	37.6	3.02	46.6	37.2	3.30	44.2	37.1	3.61	41.4	36.1	3.96	39.16	37.73	4.37	36.69	35.35	4.83
	80	67	53.6	31.3	3.08	51.4	31.0	3.36	48.9	31.2	3.68	46.2	30.4	4.02	42.94	29.64	4.41	39.88	27.39	4.86
	80	72	59.2	24.5	3.18	56.8	24.3	3.46	54.2	24.8	3.77	51.2	24.2	4.12	47.88	23.70	4.50	44.17	24.01	4.94
	75	63	49.5	30.3	3.02	47.3	29.9	3.31	44.9	29.9	3.62	41.9	29.0	3.96	39.54	26.53	4.37	36.96	28.52	4.83
1600	80	62	50.0	40.2	3.11	47.8	40.8	3.39	45.3	39.7	3.70	42.4	38.7	4.04	39.99	38.18	4.45	37.60	37.28	4.92
	80	67	54.8	33.2	3.18	52.5	34.1	3.46	49.9	33.2	3.77	47.2	32.6	4.12	43.97	32.35	4.50	40.45	31.92	4.95
	80	72	60.3	25.7	3.28	57.7	26.9	3.56	54.7	26.1	3.86	51.6	25.7	4.20	48.48	25.68	4.59	45.00	25.56	5.04
	75	63	50.7	32.1	3.12	48.5	32.8	3.40	45.9	31.8	3.71	43.0	31.0	4.05	40.18	30.74	4.45	37.49	30.50	4.92
1800	80	62	51.0	43.1	3.20	48.8	43.2	3.48	46.3	41.9	3.79	43.6	41.0	4.14	40.88	39.50	4.54	38.56	38.40	5.00
	80	67	55.8	35.6	3.27	53.4	36.0	3.55	50.8	35.0	3.86	47.9	34.7	4.21	44.76	34.21	4.60	40.87	33.80	5.03
	80	72	60.7	27.5	3.36	58.2	28.1	3.65	55.4	27.1	3.95	52.5	27.1	4.30	49.19	26.76	4.69	45.74	26.84	5.13
	75	63	51.6	34.3	3.20	49.3	34.5	3.49	46.7	33.5	3.80	43.8	33.0	4.14	40.63	32.33	4.53	37.88	32.04	5.00

**CSH4BD060K with C6BH-X60C-(C,D) + VSB**

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1750	80	62	54.5	41.2	3.63	52.3	40.4	4.06	49.9	39.5	4.54	47.2	38.1	5.08	43.9	36.5	5.73
	80	67	59.9	36.1	3.66	57.3	34.9	4.09	54.6	33.8	4.57	51.6	32.5	5.11	47.7	30.9	5.77
	80	72	65.6	30.5	3.70	62.9	29.3	4.13	60.2	28.2	4.61	56.8	26.9	5.15	52.4	25.4	5.81
	75	63	55.8	35.3	3.64	53.6	34.2	4.06	51.0	33.0	4.54	48.1	31.7	5.09	44.5	30.2	5.73
2000	80	62	57.7	45.9	3.73	55.2	44.9	4.16	52.5	44.2	4.64	49.6	42.8	5.18	46.1	40.6	5.83
	80	67	62.7	39.7	3.76	59.9	38.5	4.19	57.0	37.2	4.67	53.6	35.8	5.21	49.4	34.1	5.87
	80	72	69.4	32.8	3.81	66.2	31.7	4.24	62.7	30.5	4.71	59.0	29.2	5.25	54.2	27.5	5.91
	75	63	58.6	38.8	3.74	56.0	37.6	4.17	53.3	36.3	4.64	50.2	34.8	5.18	46.3	33.1	5.83
2250	80	62	59.9	50.3	3.87	57.3	49.4	4.30	54.4	48.3	4.77	51.3	46.6	5.31	47.2	44.1	5.97
	80	67	64.7	42.8	3.90	61.8	41.5	4.32	58.7	40.1	4.80	55.2	38.7	5.35	50.8	36.8	6.01
	80	72	71.1	35.0	3.94	67.8	33.8	4.37	64.2	32.5	4.85	60.2	31.2	5.39	55.0	29.5	6.04
	75	63	60.6	41.7	3.87	57.9	40.4	4.30	54.9	39.0	4.77	51.7	37.5	5.32	47.6	35.7	5.97

# 13 SEER + AHU COOLING EXPANDED RATINGS

**CSH4BD018K with B6BMM024K-(A,B)**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
500	80	62	17.7	14.0	1.06	16.9	13.9	1.19	16.0	13.9	1.32	15.1	13.6	1.47	14.19	13.95	1.64	13.42	13.19	1.82
	80	67	19.5	11.3	1.08	18.7	11.2	1.20	17.7	11.3	1.34	16.6	11.0	1.48	15.39	10.72	1.64	14.34	10.11	1.83
	80	72	21.6	8.8	1.10	20.7	8.8	1.23	19.7	8.9	1.36	18.7	8.7	1.51	17.45	8.50	1.67	16.05	8.60	1.85
	75	63	17.9	10.9	1.07	17.1	10.8	1.19	16.2	10.8	1.33	15.2	10.5	1.47	14.23	9.58	1.64	13.24	10.33	1.82
650	80	62	18.8	16.4	1.11	18.0	16.6	1.24	17.2	16.1	1.38	16.3	15.4	1.52	15.31	14.79	1.69	14.39	14.27	1.87
	80	67	20.5	12.9	1.13	19.6	13.2	1.26	18.5	12.9	1.39	17.4	12.7	1.53	16.17	12.57	1.69	14.86	12.74	1.88
	80	72	22.6	9.8	1.16	21.6	10.2	1.28	20.6	9.9	1.42	19.4	9.8	1.56	18.13	9.84	1.72	16.61	9.79	1.90
	75	63	18.9	12.4	1.11	18.0	12.7	1.24	17.0	12.3	1.37	15.8	12.0	1.52	14.76	11.92	1.68	13.75	12.14	1.87
800	80	62	20.0	18.2	1.17	19.2	17.9	1.29	18.3	17.1	1.43	17.4	16.5	1.58	16.33	15.77	1.74	15.07	15.01	1.92
	80	67	21.1	14.5	1.18	20.1	14.7	1.30	19.1	14.3	1.44	18.0	14.6	1.58	16.70	14.47	1.74	15.14	14.32	1.92
	80	72	23.2	11.0	1.22	22.1	11.2	1.34	21.0	10.9	1.47	19.8	10.8	1.61	18.47	10.72	1.77	17.02	10.74	1.95
	75	63	19.5	13.9	1.16	18.5	14.0	1.29	17.6	14.0	1.42	16.4	13.9	1.57	15.11	13.62	1.73	14.03	13.59	1.91

**CSH4BD024K with B6BMM024K-(A,B)**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
650	80	62	23.6	18.0	1.36	22.8	18.2	1.52	21.7	18.3	1.68	20.4	17.9	1.86	18.96	18.58	2.06	17.80	17.44	2.29
	80	67	26.0	15.0	1.38	24.9	14.9	1.53	23.7	15.0	1.70	22.4	14.6	1.88	21.00	14.26	2.08	19.37	13.10	2.30
	80	72	28.8	11.7	1.42	27.7	11.6	1.57	26.5	11.9	1.74	25.1	11.6	1.91	23.59	11.37	2.11	21.93	11.59	2.33
	75	63	23.9	14.5	1.37	23.0	14.3	1.52	21.8	14.4	1.68	20.5	14.0	1.86	19.00	12.63	2.06	17.76	13.57	2.29
800	80	62	24.8	20.7	1.42	23.8	21.1	1.57	22.6	20.6	1.74	21.5	20.2	1.92	20.36	19.67	2.12	18.95	18.79	2.34
	80	67	27.0	16.5	1.45	25.9	16.9	1.60	24.6	16.5	1.76	23.3	16.2	1.94	21.80	16.12	2.14	20.16	15.96	2.36
	80	72	29.8	12.7	1.49	28.6	13.3	1.64	27.2	12.9	1.80	25.7	12.8	1.98	23.93	12.77	2.17	22.26	12.71	2.38
	75	63	24.9	15.9	1.42	23.9	16.3	1.57	22.7	15.8	1.74	21.4	15.5	1.92	19.84	15.29	2.11	18.18	15.01	2.34
950	80	62	25.7	23.2	1.48	24.8	23.1	1.63	23.8	22.2	1.80	22.7	21.5	1.98	21.39	20.67	2.18	20.00	19.91	2.41
	80	67	27.7	18.2	1.51	26.5	18.4	1.66	25.3	17.9	1.82	23.8	17.7	2.00	22.30	17.51	2.19	20.70	17.90	2.41
	80	72	30.3	14.0	1.55	28.9	14.2	1.70	27.5	13.8	1.86	26.1	13.7	2.03	24.46	13.57	2.23	22.74	13.61	2.44
	75	63	25.6	17.5	1.48	24.5	17.6	1.63	23.3	17.1	1.79	21.9	16.9	1.97	20.43	17.03	2.17	18.53	16.73	2.39



# 13 SEER + AHU COOLING EXPANDED RATINGS (CONTINUED)

**CSH4BD030K with B6BMM030K-(A,B)**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
950	80	62	29.4	24.3	1.81	28.3	24.2	1.98	27.0	24.3	2.17	25.7	23.9	2.38	24.53	24.11	2.64	23.11	22.72	2.92
	80	67	32.2	19.2	1.86	30.9	19.1	2.04	29.5	19.3	2.22	28.0	18.9	2.43	26.42	18.63	2.67	24.64	17.63	2.95
	80	72	35.4	14.8	1.93	34.0	14.7	2.10	32.6	15.0	2.29	31.0	14.7	2.50	29.31	14.52	2.74	27.45	14.86	3.02
	75	63	29.7	18.6	1.82	28.5	18.4	1.98	27.2	18.6	2.17	25.8	18.1	2.39	24.15	16.47	2.63	22.39	17.81	2.91
1100	80	62	30.3	26.5	1.88	29.1	27.0	2.05	28.2	26.2	2.24	27.0	25.5	2.46	25.64	24.77	2.71	24.15	23.94	2.99
	80	67	32.9	20.6	1.94	31.5	21.2	2.10	30.1	20.7	2.29	28.6	20.5	2.49	26.95	20.48	2.73	25.11	20.41	3.01
	80	72	36.1	15.6	2.01	34.7	16.4	2.18	33.2	15.9	2.36	31.6	15.8	2.57	29.80	15.91	2.81	27.90	16.00	3.09
	75	63	30.4	19.9	1.88	29.2	20.4	2.05	27.8	19.9	2.24	26.3	19.6	2.45	24.67	19.48	2.69	22.95	19.95	2.97
1250	80	62	31.4	28.5	1.96	30.4	28.3	2.13	29.2	27.2	2.32	27.9	26.5	2.53	26.51	25.62	2.78	24.97	24.87	3.06
	80	67	33.4	22.3	2.00	32.1	22.5	2.17	30.6	22.0	2.35	29.0	22.0	2.56	27.32	21.81	2.80	25.52	22.67	3.08
	80	72	36.7	16.8	2.08	35.2	17.2	2.25	33.6	16.7	2.43	31.9	16.8	2.64	30.11	16.76	2.88	28.13	16.95	3.15
	75	63	30.9	21.4	1.95	29.6	21.6	2.11	28.3	21.1	2.30	26.7	20.9	2.51	25.11	21.48	2.75	23.29	21.44	3.03

**CSH4BD036K with B6BMM036K-B**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1000	80	62	35.4	27.2	2.23	34.0	26.9	2.46	32.4	27.0	2.71	30.6	26.4	2.99	28.71	27.66	3.30	26.68	25.71	3.66
	80	67	38.9	22.6	2.30	37.4	22.4	2.52	35.7	22.6	2.77	33.9	22.2	3.05	31.87	21.76	3.37	29.74	19.70	3.73
	80	72	42.8	17.6	2.38	41.2	17.5	2.61	39.4	17.8	2.86	37.5	17.5	3.15	35.39	17.17	3.47	33.13	17.56	3.84
	75	63	36.0	21.9	2.24	34.5	21.7	2.47	32.9	21.8	2.72	31.1	21.3	2.99	29.20	19.30	3.31	27.08	20.85	3.67
1150	80	62	36.4	29.2	2.30	34.8	29.7	2.52	33.2	29.0	2.77	31.4	28.5	3.05	29.54	28.10	3.37	27.60	27.37	3.73
	80	67	39.8	24.1	2.37	38.2	24.8	2.59	36.5	24.2	2.84	34.6	23.9	3.12	32.55	23.82	3.45	30.30	23.72	3.80
	80	72	43.8	18.5	2.46	42.1	19.4	2.69	40.2	18.8	2.94	38.2	18.6	3.22	36.02	18.74	3.55	33.65	18.82	3.91
	75	63	36.9	23.3	2.32	35.4	23.9	2.53	33.7	23.2	2.78	31.8	22.9	3.06	29.80	22.70	3.38	27.66	22.49	3.73
1300	80	62	37.1	31.4	2.37	35.6	31.5	2.59	33.9	30.7	2.84	32.2	30.2	3.12	30.35	29.32	3.44	28.59	28.47	3.81
	80	67	40.6	25.9	2.44	38.9	26.2	2.66	37.1	25.6	2.91	35.2	25.5	3.19	33.04	25.25	3.51	30.77	25.28	3.87
	80	72	44.5	19.8	2.53	42.7	20.3	2.76	40.8	19.7	3.01	38.7	19.7	3.29	36.35	19.65	3.61	33.99	19.85	3.98
	75	63	37.6	25.0	2.38	36.0	25.2	2.60	34.2	24.5	2.85	32.4	24.3	3.13	30.29	24.03	3.44	28.09	23.78	3.79

**CSH4BD042K with B6BMM042K-B**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	41.6	34.3	2.63	39.9	34.0	2.84	37.9	34.0	3.10	35.8	33.0	3.39	33.51	32.94	3.73	31.23	30.70	4.11
	80	67	45.7	28.3	2.67	43.9	28.1	2.89	41.8	28.3	3.15	39.5	27.7	3.44	36.99	27.23	3.77	34.20	24.97	4.14
	80	72	50.2	21.6	2.75	48.2	21.5	2.97	46.0	21.9	3.22	43.6	21.5	3.51	40.90	21.12	3.84	38.10	21.50	4.21
	75	63	42.2	27.3	2.63	40.5	27.0	2.85	38.4	27.2	3.10	36.2	26.5	3.40	33.59	23.63	3.73	30.76	25.58	4.10
1550	80	62	42.3	36.1	2.69	40.6	36.6	2.91	38.7	35.5	3.16	36.6	34.5	3.46	34.54	33.37	3.80	32.26	31.99	4.18
	80	67	46.4	29.7	2.75	44.5	30.5	2.97	42.3	29.7	3.21	40.0	29.4	3.50	37.42	29.25	3.84	34.61	28.86	4.21
	80	72	50.7	22.5	2.82	48.7	23.5	3.04	46.4	22.8	3.29	44.0	22.6	3.58	41.32	22.67	3.91	38.49	22.68	4.28
	75	63	42.9	28.6	2.70	41.0	29.3	2.91	39.0	28.5	3.17	36.7	28.0	3.46	34.03	27.53	3.79	31.02	27.01	4.16
1700	80	62	43.0	38.0	2.76	41.3	38.0	2.98	39.3	36.7	3.23	37.5	35.6	3.53	35.38	34.19	3.87	33.10	32.96	4.25
	80	67	46.9	31.5	2.82	44.9	31.9	3.03	42.7	31.1	3.28	40.3	30.9	3.57	37.76	30.38	3.90	34.88	30.27	4.28
	80	72	51.1	23.8	2.89	49.1	24.3	3.11	46.8	23.6	3.36	44.3	23.6	3.65	41.67	23.48	3.98	38.80	23.66	4.35
	75	63	43.4	30.3	2.77	41.5	30.5	2.99	39.4	29.7	3.23	37.0	29.2	3.52	34.43	28.73	3.86	31.40	28.32	4.23

**CSH4BD048K with B6BMM048K-(B,C)**

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1200	80	62	47.7	34.8	2.95	45.8	34.4	3.23	43.7	34.5	3.54	41.2	33.5	3.89	38.32	34.94	4.29	35.92	32.75	4.76
	80	67	52.4	29.2	3.02	50.4	28.9	3.30	48.2	29.2	3.61	45.7	28.5	3.97	43.03	27.88	4.37	39.90	25.20	4.82
	80	72	58.0	23.1	3.14	55.8	23.0	3.42	53.5	23.4	3.73	50.9	22.9	4.08	48.04	22.46	4.48	44.92	22.95	4.93
	75	63	48.4	28.3	2.96	46.5	28.0	3.24	44.3	28.1	3.55	41.9	27.3	3.90	38.85	24.77	4.29	36.36	26.63	4.76
1350	80	62	48.9	36.9	3.02	47.0	37.6	3.30	44.7	36.4	3.62	42.2	35.8	3.97	39.30	35.33	4.36	36.57	34.88	4.82
	80	67	53.6	30.7	3.10	51.6	31.6	3.38	49.3	30.7	3.70	46.8	30.3	4.05	43.94	30.14	4.44	40.89	29.91	4.90
	80	72	59.2	24.0	3.22	57.0	25.2	3.50	54.5	24.4	3.82	51.8	24.2	4.17	48.84	24.29	4.57	45.59	24.36	5.02
	75	63	49.6	29.7	3.03	47.7	30.5	3.32	45.4	29.6	3.63	42.9	29.0	3.98	40.04	28.69	4.37	36.95	28.26	4.83
1500	80	62	49.9	39.2	3.10	47.9	39.4	3.38	45.6	38.4	3.69	43.1	37.9	4.04	40.26	37.24	4.44	37.17	36.56	4.89
	80	67	54.7	32.6	3.18	52.6	33.1	3.46	50.2	32.2	3.77	47.6	32.0	4.12	44.72	31.59	4.52	41.59	31.54	4.97
	80	72	60.2	25.6	3.30	57.8	26.2	3.58	55.3	25.4	3.90	52.5	25.4	4.25	49.34	25.24	4.64	45.91	25.47	5.09
	75	63	50.6	31.6	3.11	48.6	31.9	3.39	46.3	30.9	3.70	43.7	30.6	4.05	40.89	30.10	4.45	37.45	29.69	4.89



# 13 SEER + AHU COOLING EXPANDED RATINGS (CONTINUED)

CSH4BD060K with B6BMM060K-C

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1450	80	62	58.3	40.8	3.54	55.9	40.3	3.90	53.2	40.3	4.29	50.0	39.2	4.74	47.19	41.30	5.28	44.22	38.70	5.88
	80	67	64.2	34.5	3.67	61.7	34.1	4.02	58.9	34.4	4.43	55.9	33.5	4.89	52.57	32.80	5.40	48.85	29.84	5.97
	80	72	70.9	27.6	3.84	68.4	27.5	4.20	65.5	28.0	4.61	61.9	27.1	5.06	58.36	26.56	5.58	54.54	27.13	6.15
	75	63	59.3	33.6	3.56	56.9	33.1	3.92	54.2	33.2	4.31	51.0	32.2	4.77	47.89	29.38	5.29	44.84	31.59	5.89
1600	80	62	59.8	42.7	3.61	57.3	43.6	3.96	54.5	42.3	4.36	51.3	41.6	4.81	48.09	41.21	5.33	45.00	40.65	5.93
	80	67	65.7	35.9	3.74	63.1	37.0	4.10	60.3	35.8	4.50	57.2	35.3	4.96	53.74	35.15	5.48	49.96	34.88	6.04
	80	72	72.5	28.5	3.92	69.8	29.9	4.28	66.4	28.8	4.68	62.9	28.4	5.13	59.39	28.52	5.66	55.50	28.57	6.23
	75	63	60.7	34.9	3.63	58.2	35.8	3.98	55.4	34.6	4.38	52.4	33.9	4.84	48.70	33.45	5.34	45.58	33.24	5.94
1750	80	62	61.0	45.2	3.67	58.4	45.4	4.02	55.6	44.2	4.42	52.4	43.7	4.88	48.78	42.63	5.38	45.61	42.50	5.98
	80	67	67.0	37.9	3.81	64.3	38.3	4.17	61.4	37.2	4.57	58.2	37.0	5.03	54.74	36.54	5.54	51.00	36.53	6.11
	80	72	73.8	30.1	4.00	70.5	30.7	4.35	67.3	29.6	4.75	63.9	29.6	5.20	60.24	29.43	5.73	56.29	29.75	6.30
	75	63	61.9	36.8	3.69	59.4	37.1	4.04	56.5	35.9	4.44	53.3	35.5	4.90	49.78	34.80	5.40	46.26	34.65	5.98

# 13 SEER + LOOSE COIL HEATING EXPANDED RATINGS

CSH4BD018K / C7B(A,H)M01824(C,U)-A

100 CFM	Indoor T. Deg.F	OUTDOOR TEMPERATURE (Deg. F)																							
		10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
480	60	9.9	2.03	1.43	12.1	2.41	1.47	13.0	2.57	1.49	16.2	3.08	1.54	19.3	3.55	1.60	21.5	3.86	1.63	22.4	3.99	1.65	25.6	4.40	1.71
	70	9.4	2.01	1.36	11.4	2.35	1.42	12.3	2.49	1.45	15.1	2.91	1.53	18.0	3.29	1.61	20.1	3.53	1.67	20.9	3.63	1.69	23.8	3.94	1.77
	80	8.8	1.95	1.32	10.6	2.25	1.39	11.4	2.37	1.41	14.1	2.73	1.51	16.7	3.06	1.60	18.6	3.26	1.67	19.4	3.34	1.70	22.0	3.60	1.79
580	60	9.9	1.98	1.47	12.2	2.37	1.51	13.1	2.53	1.53	16.3	3.04	1.58	19.5	3.51	1.63	21.8	3.83	1.67	22.7	3.96	1.68	25.9	4.38	1.74
	70	9.5	1.96	1.42	11.5	2.30	1.47	12.4	2.44	1.49	15.4	2.86	1.57	18.3	3.25	1.65	20.3	3.50	1.71	21.2	3.60	1.73	24.2	3.92	1.81
	80	8.9	1.92	1.36	10.8	2.22	1.43	11.6	2.34	1.46	14.3	2.70	1.55	17.0	3.02	1.65	18.9	3.23	1.72	19.7	3.31	1.75	22.4	3.57	1.84
680	60	10.1	1.95	1.52	12.4	2.34	1.55	13.3	2.50	1.57	16.6	3.00	1.62	19.8	3.49	1.66	22.0	3.81	1.70	23.0	3.94	1.71	26.2	4.37	1.76
	70	9.6	1.93	1.45	11.7	2.27	1.51	12.6	2.41	1.53	15.6	2.84	1.61	18.6	3.23	1.68	20.6	3.48	1.74	21.5	3.59	1.76	24.5	3.91	1.84
	80	9.0	1.89	1.40	10.9	2.18	1.47	11.8	2.30	1.50	14.5	2.66	1.60	17.2	2.98	1.69	19.1	3.18	1.76	19.9	3.26	1.79	22.6	3.52	1.89

CSH4BD024K / C7B(A,H)M01824(C,U)-B

100 CFM	Indoor T. Deg.F	OUTDOOR TEMPERATURE (Deg. F)																							
		10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
755	60	12.4	2.25	1.61	15.0	2.59	1.70	16.2	2.72	1.74	20.0	3.12	1.87	23.8	3.47	2.01	26.4	3.69	2.10	27.6	3.78	2.14	31.4	4.05	2.27
	70	11.8	2.20	1.57	14.3	2.48	1.69	15.4	2.59	1.74	18.9	2.92	1.90	22.5	3.20	2.06	25.0	3.37	2.18	26.1	3.43	2.22	29.6	3.64	2.39
	80	11.2	2.11	1.56	13.5	2.35	1.68	14.5	2.45	1.74	17.9	2.72	1.92	21.2	2.95	2.11	23.5	3.09	2.23	24.5	3.14	2.29	27.9	3.30	2.47
855	60	12.4	2.21	1.65	15.1	2.55	1.74	16.3	2.68	1.78	20.1	3.10	1.91	24.0	3.46	2.04	26.7	3.68	2.13	27.9	3.77	2.17	31.8	4.05	2.30
	70	11.9	2.15	1.62	14.4	2.44	1.73	15.5	2.56	1.78	19.1	2.90	1.94	22.8	3.18	2.10	25.3	3.36	2.21	26.4	3.43	2.25	30.0	3.65	2.41
	80	11.3	2.08	1.60	13.7	2.33	1.72	14.7	2.42	1.78	18.1	2.71	1.96	21.5	2.94	2.14	23.9	3.08	2.27	24.9	3.14	2.33	28.3	3.31	2.51
955	60	12.5	2.17	1.69	15.3	2.52	1.78	16.4	2.65	1.82	20.3	3.07	1.94	24.2	3.44	2.07	27.0	3.67	2.15	28.1	3.77	2.19	32.0	4.06	2.32
	70	12.0	2.13	1.66	14.6	2.42	1.77	15.7	2.54	1.81	19.3	2.88	1.97	23.0	3.18	2.12	25.6	3.36	2.23	26.7	3.43	2.28	30.4	3.65	2.44
	80	11.4	2.05	1.64	13.8	2.30	1.76	14.9	2.40	1.82	18.3	2.68	2.00	21.7	2.92	2.18	24.1	3.06	2.30	25.1	3.12	2.36	28.5	3.29	2.54

CSH4BD030K / C7B(A,H)M03036(C,U)-A

100 CFM	Indoor T. Deg.F	OUTDOOR TEMPERATURE (Deg. F)																							
		10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
910	60	16.0	2.41	1.94	19.2	2.81	2.01	20.6	2.97	2.04	25.2	3.48	2.13	29.8	3.94	2.22	33.1	4.25	2.28	34.4	4.37	2.31	39.1	4.77	2.40
	70	15.3	2.30	1.96	18.4	2.65	2.04	19.7	2.79	2.07	24.1	3.24	2.18	28.5	3.64	2.30	31.6	3.90	2.37	32.9	4.01	2.41	37.3	4.34	2.52
	80	14.8	2.17	1.99	17.7	2.49	2.08	18.9	2.62	2.12	23.1	3.02	2.24	27.3	3.38	2.37	30.2	3.61	2.45	31.4	3.70	2.49	35.6	3.99	2.62
1010	60	16.0	2.37	1.98	19.3	2.77	2.04	20.7	2.94	2.07	25.4	3.45	2.16	30.1	3.93	2.25	33.4	4.24	2.31	34.8	4.37	2.33	39.4	4.78	2.42
	70	15.5	2.27	2.00	18.6	2.62	2.08	19.9	2.77	2.11	24.4	3.22	2.22	28.8	3.63	2.33	31.9	3.90	2.40	33.2	4.01	2.43	37.7	4.35	2.54
	80	14.9	2.15	2.03	17.8	2.47	2.11	19.1	2.60	2.15	23.3	3.01	2.28	27.6	3.37	2.40	30.5	3.60	2.49	31.8	3.69	2.52	36.0	3.99	2.65
1110	60	16.1	2.34	2.02	19.4	2.74	2.08	20.9	2.90	2.11	25.6	3.43	2.19	30.3	3.91	2.27	33.6	4.23	2.33	35.0	4.36	2.36	39.8	4.77	2.44
	70	15.6	2.25	2.03	18.7	2.61	2.11	20.1	2.75	2.14	24.6	3.21	2.25	29.1	3.62	2.35	32.2	3.89	2.43	33.6	4.00	2.46	38.0	4.35	2.56
	80	15.0	2.13	2.06	18.0	2.45	2.15	19.3	2.58	2.19	23.5	2.99	2.31	27.8	3.35	2.43	30.7	3.58	2.52	32.0	3.68	2.55	36.3	3.97	2.67

# 13 SEER + LOOSE COIL HEATING EXPANDED RATINGS (CONTINUED)

CSH4BD036K / C7B(A,H)M03036(C,U)-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1030	60	20.4	2.62	2.29	24.2	2.97	2.39	25.7	3.11	2.43	31.0	3.54	2.57	36.3	3.93	2.71	40.0	4.18	2.81	41.6	4.28	2.85	46.9	4.60	2.99
	70	19.7	2.45	2.36	23.3	2.76	2.47	24.8	2.89	2.52	29.9	3.28	2.68	35.0	3.62	2.84	38.6	3.84	2.95	40.1	3.93	3.00	45.2	4.20	3.15
	80	19.2	2.29	2.45	22.6	2.58	2.57	24.0	2.69	2.62	28.9	3.03	2.80	33.8	3.34	2.97	37.2	3.53	3.09	38.7	3.61	3.14	43.5	3.85	3.32
1180	60	20.6	2.58	2.34	24.4	2.94	2.43	26.0	3.08	2.47	31.4	3.53	2.61	36.8	3.93	2.74	40.5	4.19	2.83	42.1	4.30	2.87	47.5	4.64	3.01
	70	19.9	2.42	2.41	23.5	2.74	2.52	25.1	2.87	2.57	30.3	3.27	2.72	35.4	3.62	2.87	39.1	3.85	2.97	40.6	3.94	3.02	45.8	4.23	3.17
	80	19.3	2.26	2.50	22.8	2.55	2.62	24.3	2.67	2.67	29.3	3.03	2.84	34.2	3.34	3.00	37.7	3.55	3.12	39.2	3.63	3.17	44.2	3.88	3.34
1330	60	20.7	2.54	2.39	24.5	2.90	2.48	26.2	3.05	2.52	31.6	3.51	2.65	37.1	3.92	2.77	41.0	4.19	2.87	42.6	4.30	2.90	48.1	4.65	3.03
	70	20.1	2.40	2.46	23.8	2.72	2.56	25.4	2.85	2.61	30.6	3.26	2.75	35.8	3.63	2.90	39.5	3.86	3.00	41.1	3.96	3.05	46.3	4.25	3.19
	80	19.5	2.24	2.55	23.0	2.54	2.66	24.5	2.65	2.71	29.5	3.02	2.87	34.6	3.34	3.03	38.1	3.55	3.15	39.6	3.63	3.20	44.6	3.90	3.36

CSH4BD042K / C7B(A,H)M03642(C,U)-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1170	60	22.0	2.50	2.58	25.9	2.74	2.78	27.6	2.83	2.86	33.1	3.10	3.13	38.7	3.33	3.41	42.6	3.47	3.60	44.3	3.52	3.69	49.8	3.69	3.96
	70	21.2	2.30	2.70	25.0	2.52	2.91	26.6	2.60	3.00	32.0	2.84	3.31	37.4	3.04	3.61	41.1	3.16	3.82	42.8	3.21	3.91	48.1	3.35	4.21
	80	20.7	2.14	2.84	24.3	2.32	3.07	25.9	2.39	3.17	31.0	2.60	3.50	36.2	2.77	3.82	39.8	2.88	4.05	41.3	2.92	4.15	46.5	3.04	4.48
1320	60	22.2	2.47	2.63	26.1	2.72	2.81	27.8	2.82	2.89	33.5	3.11	3.16	39.1	3.35	3.43	43.1	3.50	3.61	44.8	3.56	3.69	50.4	3.74	3.96
	70	21.5	2.29	2.75	25.3	2.51	2.95	26.9	2.60	3.04	32.4	2.85	3.33	37.8	3.06	3.62	41.6	3.19	3.82	43.2	3.25	3.91	48.7	3.40	4.20
	80	20.9	2.12	2.89	24.5	2.31	3.11	26.1	2.39	3.20	31.3	2.61	3.52	36.6	2.80	3.83	40.3	2.91	4.05	41.8	2.96	4.15	47.1	3.09	4.46
1470	60	22.2	2.44	2.67	26.2	2.70	2.85	28.0	2.80	2.93	33.7	3.10	3.19	39.5	3.35	3.45	43.5	3.51	3.63	45.2	3.57	3.71	51.0	3.76	3.97
	70	21.7	2.28	2.79	25.5	2.50	2.99	27.2	2.59	3.08	32.7	2.86	3.36	38.2	3.08	3.64	42.1	3.22	3.83	43.7	3.27	3.92	49.2	3.44	4.20
	80	21.1	2.11	2.93	24.8	2.31	3.15	26.3	2.39	3.24	31.6	2.62	3.54	36.9	2.82	3.85	40.6	2.94	4.06	42.2	2.98	4.15	47.5	3.13	4.45

CSH4BD048K / C7B(A,H)M03648(C,U)-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1195	60	26.5	2.55	3.06	31.4	2.88	3.19	33.5	3.02	3.25	40.4	3.43	3.45	47.3	3.81	3.65	52.2	4.04	3.78	54.2	4.14	3.84	61.2	4.44	4.04
	70	25.7	2.32	3.24	30.4	2.63	3.39	32.4	2.76	3.45	39.2	3.14	3.66	46.0	3.48	3.87	50.7	3.70	4.01	52.7	3.79	4.08	59.5	4.07	4.29
	80	25.2	2.14	3.45	29.7	2.42	3.61	31.7	2.53	3.67	38.3	2.88	3.90	44.8	3.19	4.12	49.4	3.39	4.27	51.3	3.47	4.34	57.9	3.72	4.56
1395	60	26.8	2.53	3.10	31.7	2.88	3.23	33.8	3.02	3.29	40.9	3.45	3.47	47.9	3.84	3.66	52.8	4.09	3.79	55.0	4.19	3.84	62.0	4.51	4.03
	70	26.0	2.32	3.29	30.8	2.64	3.43	32.9	2.76	3.48	39.7	3.16	3.68	46.6	3.52	3.88	51.4	3.75	4.01	53.4	3.85	4.07	60.3	4.14	4.27
	80	25.4	2.12	3.50	30.0	2.42	3.65	32.0	2.53	3.71	38.7	2.90	3.92	45.4	3.23	4.12	50.0	3.44	4.26	52.0	3.53	4.33	58.7	3.80	4.53
1595	60	26.9	2.50	3.15	31.9	2.86	3.27	34.0	3.00	3.33	41.2	3.45	3.51	48.4	3.85	3.69	53.4	4.11	3.81	55.6	4.22	3.87	62.8	4.55	4.05
	70	26.3	2.31	3.34	31.2	2.64	3.47	33.3	2.77	3.53	40.2	3.18	3.71	47.1	3.54	3.90	52.0	3.78	4.03	54.0	3.88	4.08	61.0	4.19	4.27
	80	25.7	2.12	3.55	30.4	2.42	3.69	32.4	2.54	3.75	39.1	2.91	3.94	45.9	3.25	4.13	50.6	3.47	4.27	52.6	3.56	4.33	59.3	3.85	4.52

CSH4BD060K with C6BH-X60C-(C,D) + VSB

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1650	60	33.7	2.68	3.69	37.8	2.88	3.86	39.6	2.96	3.93	45.6	3.21	4.17	51.6	3.43	4.42	55.8	3.57	4.59	57.6	3.63	4.66	63.6	3.80	4.90
	70	32.7	2.41	3.97	36.8	2.60	4.15	38.5	2.68	4.22	44.4	2.91	4.47	50.3	3.12	4.72	54.4	3.26	4.89	56.1	3.31	4.96	62.0	3.49	5.21
	80	32.2	2.21	4.28	36.2	2.38	4.46	37.8	2.44	4.54	43.5	2.66	4.80	49.1	2.84	5.06	53.0	2.97	5.24	54.7	3.02	5.32	60.4	3.17	5.58
1850	60	34.0	2.68	3.72	38.2	2.89	3.88	40.0	2.98	3.95	46.1	3.24	4.18	52.2	3.48	4.41	56.5	3.63	4.57	58.3	3.69	4.63	64.4	3.88	4.86
	70	33.0	2.42	4.00	37.2	2.62	4.16	39.0	2.70	4.23	44.9	2.95	4.46	50.8	3.17	4.70	55.0	3.32	4.86	56.8	3.38	4.93	62.7	3.56	5.16
	80	32.4	2.20	4.31	36.5	2.39	4.48	38.2	2.46	4.55	43.9	2.69	4.79	49.7	2.89	5.03	53.7	3.03	5.20	55.4	3.08	5.27	61.2	3.25	5.51
2050	60	33.9	2.65	3.75	38.3	2.88	3.91	40.2	2.97	3.97	46.5	3.25	4.20	52.7	3.50	4.42	57.1	3.66	4.58	59.0	3.72	4.64	65.2	3.93	4.87
	70	33.4	2.43	4.04	37.6	2.63	4.19	39.4	2.71	4.26	45.4	2.97	4.48	51.4	3.21	4.70	55.6	3.36	4.85	57.4	3.42	4.92	63.4	3.62	5.14
	80	32.7	2.21	4.35	36.8	2.40	4.51	38.6	2.47	4.57	44.4	2.71	4.80	50.2	2.93	5.02	54.2	3.07	5.18	56.0	3.13	5.24	61.8	3.32	5.47

# 13 SEER + AHU HEATING EXPANDED RATINGS

CSH4BD018K with B6BMM024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
545	60	9.2	2.02	1.33	11.4	2.40	1.40	12.4	2.55	1.42	15.6	3.01	1.52	18.8	3.42	1.61	21.0	3.68	1.68	22.0	3.78	1.71	25.2	4.11	1.80
	70	8.7	2.03	1.25	10.7	2.35	1.34	11.6	2.47	1.38	14.6	2.84	1.50	17.5	3.16	1.63	19.6	3.35	1.71	20.5	3.43	1.75	23.4	3.66	1.88
	80	8.0	1.98	1.19	9.9	2.26	1.29	10.8	2.36	1.34	13.5	2.67	1.48	16.2	2.93	1.62	18.1	3.08	1.72	18.9	3.14	1.76	21.6	3.32	1.91
645	60	9.2	1.96	1.37	11.5	2.34	1.44	12.5	2.50	1.47	15.7	2.97	1.56	19.0	3.38	1.65	21.3	3.65	1.71	22.3	3.76	1.74	25.6	4.10	1.83
	70	8.8	1.97	1.30	10.9	2.29	1.39	11.8	2.42	1.43	14.8	2.80	1.55	17.8	3.13	1.67	19.9	3.33	1.75	20.8	3.41	1.79	23.8	3.65	1.91
	80	8.2	1.94	1.23	10.1	2.22	1.34	10.9	2.33	1.38	13.7	2.64	1.52	16.5	2.90	1.67	18.4	3.06	1.77	19.3	3.12	1.81	22.1	3.30	1.96
745	60	9.4	1.94	1.42	11.7	2.31	1.48	12.7	2.47	1.51	16.0	2.94	1.59	19.2	3.36	1.68	21.5	3.63	1.74	22.5	3.74	1.77	25.8	4.09	1.85
	70	8.9	1.93	1.34	11.0	2.26	1.43	11.9	2.39	1.46	15.0	2.78	1.58	18.0	3.11	1.70	20.2	3.31	1.79	21.1	3.40	1.82	24.2	3.65	1.94
	80	8.3	1.91	1.28	10.3	2.18	1.38	11.1	2.29	1.42	13.9	2.60	1.57	16.7	2.86	1.71	18.6	3.01	1.81	19.5	3.08	1.86	22.3	3.26	2.00

CSH4BD024K with B6BMM024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
720	60	13.2	2.38	1.63	15.8	2.72	1.70	16.9	2.86	1.73	20.6	3.28	1.84	24.2	3.65	1.95	26.8	3.89	2.02	27.9	3.98	2.06	31.6	4.28	2.16
	70	12.6	2.32	1.59	15.0	2.61	1.69	16.1	2.73	1.73	19.5	3.07	1.86	23.0	3.37	2.00	25.4	3.56	2.09	26.4	3.63	2.13	29.8	3.86	2.27
	80	12.0	2.23	1.58	14.3	2.48	1.69	15.2	2.58	1.73	18.5	2.87	1.88	21.7	3.12	2.04	23.9	3.27	2.14	24.9	3.33	2.19	28.1	3.52	2.34
820	60	13.3	2.33	1.67	15.9	2.68	1.74	17.0	2.81	1.77	20.7	3.24	1.88	24.5	3.63	1.98	27.1	3.87	2.05	28.2	3.97	2.08	32.0	4.28	2.19
	70	12.7	2.28	1.64	15.2	2.57	1.73	16.2	2.69	1.77	19.7	3.04	1.90	23.2	3.35	2.03	25.7	3.54	2.12	26.7	3.62	2.16	30.2	3.86	2.29
	80	12.1	2.20	1.62	14.4	2.45	1.72	15.4	2.55	1.77	18.7	2.85	1.92	22.0	3.11	2.07	24.3	3.26	2.18	25.2	3.32	2.23	28.5	3.52	2.38
920	60	13.4	2.29	1.71	16.0	2.64	1.78	17.2	2.78	1.81	20.9	3.21	1.91	24.7	3.61	2.01	27.4	3.86	2.08	28.5	3.96	2.11	32.3	4.28	2.21
	70	12.8	2.25	1.68	15.3	2.54	1.77	16.4	2.66	1.81	19.9	3.02	1.93	23.5	3.34	2.06	26.0	3.54	2.15	27.0	3.62	2.19	30.6	3.87	2.32
	80	12.3	2.17	1.66	14.6	2.42	1.76	15.6	2.52	1.81	18.9	2.82	1.96	22.1	3.08	2.11	24.5	3.24	2.22	25.4	3.30	2.26	28.7	3.49	2.41

CSH4BD030K with B6BMM030K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
930	60	16.6	2.46	1.98	19.8	2.74	2.12	21.1	2.84	2.18	25.7	3.16	2.38	30.2	3.43	2.59	33.4	3.59	2.73	34.8	3.66	2.79	39.3	3.85	2.99
	70	15.9	2.34	2.00	19.0	2.57	2.16	20.3	2.66	2.23	24.6	2.92	2.47	28.9	3.14	2.70	31.9	3.27	2.86	33.2	3.33	2.93	37.6	3.48	3.16
	80	15.4	2.21	2.04	18.2	2.41	2.22	19.5	2.48	2.30	23.6	2.70	2.56	27.6	2.88	2.81	30.5	2.99	2.99	31.7	3.03	3.07	35.8	3.16	3.33
1080	60	16.7	2.41	2.03	20.0	2.70	2.17	21.4	2.81	2.23	26.0	3.15	2.42	30.6	3.43	2.62	33.9	3.60	2.76	35.2	3.67	2.81	39.9	3.89	3.01
	70	16.1	2.29	2.06	19.2	2.54	2.22	20.5	2.63	2.29	24.9	2.91	2.51	29.3	3.15	2.73	32.4	3.29	2.89	33.7	3.35	2.96	38.1	3.52	3.18
	80	15.5	2.17	2.10	18.5	2.38	2.28	19.7	2.46	2.35	23.9	2.70	2.60	28.1	2.89	2.85	31.0	3.01	3.02	32.3	3.05	3.10	36.5	3.19	3.35
1230	60	16.9	2.37	2.08	20.1	2.67	2.22	21.6	2.78	2.27	26.3	3.13	2.46	31.0	3.42	2.65	34.3	3.61	2.79	35.7	3.68	2.84	40.4	3.90	3.03
	70	16.3	2.27	2.11	19.4	2.52	2.26	20.8	2.62	2.33	25.3	2.91	2.55	29.7	3.15	2.77	32.8	3.30	2.92	34.2	3.36	2.98	38.7	3.54	3.20
	80	15.7	2.14	2.16	18.7	2.36	2.33	20.0	2.44	2.40	24.2	2.68	2.64	28.4	2.89	2.88	31.4	3.01	3.05	32.6	3.06	3.13	36.9	3.21	3.37

CSH4BD036K with B6BMM036K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1035	60	19.2	2.51	2.24	22.9	2.83	2.37	24.5	2.97	2.42	29.8	3.36	2.60	35.1	3.70	2.78	38.8	3.92	2.90	40.4	4.01	2.96	45.7	4.28	3.14
	70	18.5	2.35	2.31	22.1	2.64	2.45	23.6	2.76	2.51	28.7	3.10	2.71	33.8	3.40	2.91	37.4	3.59	3.05	38.9	3.66	3.11	44.0	3.89	3.32
	80	17.9	2.20	2.39	21.3	2.46	2.55	22.8	2.56	2.61	27.7	2.87	2.83	32.6	3.13	3.05	36.0	3.29	3.21	37.4	3.35	3.27	42.3	3.55	3.50
1185	60	19.3	2.47	2.30	23.1	2.81	2.42	24.7	2.94	2.47	30.1	3.35	2.64	35.5	3.71	2.81	39.3	3.94	2.93	40.9	4.03	2.98	46.3	4.31	3.15
	70	18.7	2.32	2.36	22.3	2.62	2.50	23.9	2.74	2.56	29.0	3.10	2.75	34.2	3.41	2.94	37.8	3.61	3.08	39.4	3.69	3.13	44.6	3.93	3.33
	80	18.1	2.17	2.45	21.6	2.44	2.59	23.1	2.54	2.66	28.0	2.86	2.87	33.0	3.14	3.08	36.5	3.31	3.23	38.0	3.38	3.30	42.9	3.59	3.51
1335	60	19.4	2.43	2.34	23.3	2.77	2.46	24.9	2.91	2.51	30.4	3.33	2.68	35.9	3.70	2.84	39.7	3.94	2.96	41.4	4.03	3.01	46.9	4.33	3.18
	70	18.9	2.30	2.41	22.6	2.60	2.54	24.1	2.72	2.60	29.4	3.09	2.79	34.6	3.42	2.97	38.3	3.62	3.10	39.9	3.70	3.16	45.1	3.95	3.35
	80	18.3	2.15	2.49	21.8	2.42	2.64	23.3	2.53	2.70	28.3	2.86	2.91	33.3	3.14	3.11	36.8	3.32	3.26	38.3	3.39	3.32	43.4	3.61	3.53

# 13 SEER + AHU HEATING EXPANDED RATINGS (CONTINUED)

## CSH4BD042K with B6BMM042K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1385	60	22.4	2.41	2.72	26.3	2.65	2.91	27.9	2.74	2.98	33.4	3.02	3.24	38.9	3.26	3.50	42.7	3.40	3.68	44.3	3.46	3.76	49.8	3.63	4.02
	70	21.7	2.22	2.87	25.4	2.43	3.06	27.0	2.51	3.15	32.2	2.76	3.43	37.5	2.97	3.71	41.2	3.10	3.90	42.8	3.15	3.99	48.1	3.31	4.27
	80	21.1	2.05	3.02	24.7	2.24	3.24	26.2	2.31	3.33	31.3	2.52	3.63	36.3	2.71	3.94	39.9	2.82	4.15	41.4	2.86	4.24	46.4	3.00	4.55
1535	60	22.6	2.39	2.77	26.5	2.64	2.94	28.2	2.74	3.02	33.7	3.03	3.27	39.3	3.28	3.51	43.2	3.43	3.69	44.9	3.49	3.76	50.4	3.68	4.01
	70	21.9	2.21	2.91	25.6	2.43	3.10	27.2	2.51	3.18	32.6	2.77	3.45	38.0	3.00	3.72	41.7	3.13	3.91	43.3	3.19	3.99	48.7	3.35	4.26
	80	21.3	2.03	3.07	24.9	2.23	3.27	26.4	2.31	3.36	31.6	2.54	3.65	36.7	2.73	3.94	40.4	2.85	4.15	41.9	2.90	4.23	47.1	3.05	4.52
1685	60	22.6	2.37	2.81	26.6	2.62	2.98	28.3	2.72	3.05	34.0	3.02	3.30	39.6	3.28	3.54	43.6	3.45	3.71	45.3	3.51	3.78	51.0	3.71	4.03
	70	22.1	2.20	2.95	25.9	2.42	3.13	27.5	2.51	3.21	33.0	2.78	3.47	38.4	3.01	3.73	42.2	3.16	3.92	43.8	3.21	4.00	49.2	3.39	4.26
	80	21.5	2.03	3.11	25.1	2.23	3.31	26.7	2.31	3.39	31.9	2.55	3.67	37.1	2.75	3.95	40.7	2.88	4.15	42.3	2.93	4.23	47.5	3.09	4.51

## CSH4BD048K with B6BMM048K-(B,C)

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1160	60	26.2	2.59	2.97	30.9	2.83	3.20	32.8	2.92	3.30	39.4	3.19	3.63	46.1	3.42	3.95	50.7	3.56	4.18	52.7	3.61	4.28	59.3	3.77	4.60
	70	25.4	2.36	3.15	29.9	2.58	3.40	31.8	2.66	3.50	38.3	2.91	3.85	44.7	3.12	4.20	49.2	3.25	4.45	51.2	3.30	4.55	57.6	3.45	4.90
	80	24.9	2.18	3.35	29.2	2.37	3.62	31.1	2.44	3.73	37.3	2.66	4.11	43.5	2.84	4.49	47.9	2.95	4.75	49.8	3.00	4.87	56.0	3.13	5.24
1360	60	26.5	2.57	3.02	31.2	2.82	3.24	33.2	2.92	3.33	39.9	3.21	3.64	46.6	3.46	3.95	51.3	3.61	4.17	53.4	3.67	4.26	60.1	3.85	4.58
	70	25.7	2.35	3.20	30.3	2.59	3.44	32.2	2.67	3.53	38.8	2.94	3.87	45.3	3.16	4.20	49.9	3.30	4.43	51.8	3.35	4.53	58.3	3.52	4.86
	80	25.1	2.16	3.41	29.5	2.37	3.66	31.4	2.45	3.76	37.8	2.69	4.12	44.1	2.89	4.48	48.5	3.01	4.73	50.4	3.06	4.83	56.8	3.21	5.19
1560	60	26.6	2.54	3.07	31.4	2.80	3.28	33.4	2.91	3.37	40.3	3.21	3.67	47.1	3.48	3.98	51.9	3.64	4.19	54.0	3.70	4.28	60.8	3.89	4.58
	70	26.1	2.35	3.26	30.7	2.59	3.48	32.7	2.68	3.58	39.2	2.96	3.89	45.8	3.19	4.21	50.5	3.34	4.44	52.4	3.39	4.53	59.0	3.57	4.85
	80	25.4	2.15	3.46	29.9	2.37	3.70	31.8	2.45	3.80	38.2	2.71	4.14	44.6	2.92	4.48	49.1	3.05	4.72	51.0	3.10	4.82	57.4	3.26	5.16

## CSH4BD060K with B6BMM060K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1400	60	30.3	2.29	3.88	36.4	2.56	4.17	39.0	2.67	4.29	47.7	2.97	4.70	56.4	3.23	5.12	62.5	3.39	5.41	65.1	3.45	5.53	73.8	3.64	5.94
	70	29.4	2.05	4.20	35.4	2.30	4.50	37.9	2.40	4.63	46.5	2.69	5.06	55.0	2.94	5.49	61.0	3.09	5.79	63.6	3.15	5.92	72.1	3.33	6.34
	80	28.9	1.87	4.54	34.7	2.10	4.86	37.2	2.18	5.00	45.6	2.45	5.46	53.9	2.67	5.92	59.7	2.81	6.24	62.3	2.86	6.38	70.6	3.03	6.84
1600	60	30.6	2.30	3.91	36.8	2.58	4.18	39.4	2.69	4.30	48.2	3.01	4.69	57.0	3.29	5.09	63.2	3.46	5.36	65.8	3.52	5.48	74.6	3.73	5.87
	70	29.7	2.07	4.22	35.8	2.33	4.50	38.4	2.43	4.63	47.0	2.74	5.03	55.6	3.00	5.44	61.7	3.16	5.73	64.3	3.22	5.85	72.9	3.42	6.26
	80	29.1	1.87	4.57	35.0	2.11	4.87	37.6	2.20	5.00	46.0	2.49	5.43	54.5	2.73	5.86	60.4	2.88	6.16	62.9	2.94	6.28	71.4	3.12	6.71
1800	60	30.6	2.28	3.93	36.9	2.57	4.20	39.6	2.69	4.32	48.6	3.03	4.70	57.5	3.31	5.09	63.8	3.49	5.36	66.5	3.56	5.48	75.5	3.77	5.86
	70	30.1	2.07	4.26	36.2	2.34	4.53	38.8	2.45	4.65	47.5	2.76	5.04	56.2	3.04	5.43	62.3	3.20	5.70	64.9	3.27	5.82	73.6	3.48	6.21
	80	29.4	1.87	4.60	35.4	2.12	4.89	37.9	2.22	5.01	46.5	2.52	5.41	55.0	2.77	5.82	61.0	2.93	6.10	63.5	2.99	6.23	72.0	3.19	6.63



We Encourage Professionalism



Through Technician Certification by NATE



**MAYTAG**

Before purchasing this appliance, read important energy cost and efficiency information available from your retailer. Specifications and illustrations subject to change without notice and without incurring obligations.

Manufactured under license by NORDYNE, O'Fallon, MO. ®Registered Trademark/™ Trademark of Maytag Corporation or its related companies. ©2012. All rights reserved.

710D-0112 (Replaces 710D-0911)

Printed in U.S.A. (01/12)